



# **24X36**PORCELAIN PAVERS

DATA SHEET



### **TECHNICAL DETAILS**

1. Water Absorption: ≤ 0.06%

2. Modulus of Rupture: ≥ 5076 psi

3. **Breaking Strength:**  $\geq$  292 lbs (for thickness  $\geq$  7.5 mm),  $\geq$  157 lbs (for thickness < 7.5 mm)

4. Resistance to Deep Abrasion: < 0.0107 in<sup>3</sup>

5. Coefficient of Linear Thermal Expansion: < 7.1 x 10<sup>-6</sup> /°F

6. Thermal Shock Resistance: Complies

7. **Crazing Resistance:** Complies 8. **Frost Resistance:** Complies

o. 11 ost resistance. compiles

9. **Moisture Expansion:** ≤ 0.00787 in/ft

10. Impact Resistance: Coefficient of Restitution > 0.75

11. Reaction to Fire: Class A1 or A1FL

12. Mohs Hardness:  $\geq 5$ 

13. **Chemical Resistance:** Minimum class B, Resistant to household chemicals and swimming pool salts

14. **Resistance to Staining:** Class 5

15. **Release of Dangerous Substances:** Pb < 0.1 mg/dm<sup>2</sup>, Cd < 0.01 mg/dm<sup>2</sup>

16. Dimensions: Complies

17. **Surface Quality:** Minimum 95% free from visible

defects

18. Slip Resistance: R10 A+B

### **FEATURES**

The 24x36 porcelain pavers by NT Pavers offer a perfect blend of style and durability for outdoor environments. Each paver, measuring a substantial 24 inches by 36 inches, provides a robust foundation for a variety of outdoor spaces. With a practical thickness, these pavers ensure ease of installation and a smooth, cohesive appearance.

## **PACKAGING DETAILS**

**24x36:** 1 pallet = 288 sqft (48 pcs/pallet. 1 pc/bx)





# DATA SHEET 24X36 PORCELAIN PAVERS



Basalto Red

# **AVAILABLE COLORS**



Light Grey



Basalto Black



Dark Grey



Bluestone



**Basalto Grey** 



**Urban White**