



## DATA SHEET **WOOD LOOK**

### PORCELAIN PAVERS







#### **TECHNICAL DETAILS**

1. Water Absorption: ≤ 0.06%

2. Modulus of Rupture: ≥ 5076 psi

3. **Breaking Strength:**  $\geq$  292 lbs (for thickness  $\geq$  7.5 mm),  $\geq$  157 lbs (for thickness < 7.5 mm)

4. Resistance to Deep Abrasion: < 0.0107 in<sup>3</sup>

5. Coefficient of Linear Thermal Expansion: < 7.1 x 10<sup>-6</sup> /°F

6. Thermal Shock Resistance: Complies

7. Crazing Resistance: Complies 8. Frost Resistance: Complies

9. **Moisture Expansion:** ≤ 0.00787 in/ft

10. **Impact Resistance**: Coefficient of Restitution > 0.75

11. Reaction to Fire: Class A1 or A1FL

12. Mohs Hardness:  $\geq 5$ 

13. Chemical Resistance: Minimum class B, Resistant to household chemicals and swimming pool salts

14. Resistance to Staining: Class 5

15. Release of Dangerous Substances: Pb < 0.1  $mg/dm^2$ ,  $Cd < 0.01 mg/dm^2$ 

16. **Dimensions:** Complies

17. Surface Quality: Minimum 95% free from visible

defects

18. Slip Resistance: R10 A+B

#### **FEATURES**

The wood look porcelain pavers by NT Pavers offer a perfect blend of style and durability for outdoor environments. Each paver, measuring 8 inches by 48 inches and 16 inches by 48 inches, provides a robust foundation for a variety of outdoor spaces. With a practical thickness, these pavers ensure ease of installation and a smooth, cohesive appearance.

#### **PACKAGING DETAILS**

**8x48:** 1 pallet = 213 sqft (80 pcs/pallet. 2 pc/bx)

**16x48:** 1 pallet = 256 sqft (48 pcs/pallet. 1 pc/bx)





# DATA SHEET WOOD LOOK PORCELAIN PAVERS



20cm x 120cm (7.87" x 47.24")



**AVAILABLE COLORS** 



Alpin



Timber



Clay