



DATA SHEET **24X48 & 32X72**

PORCELAIN PAVERS



60cm x 120cm (23.62" x 47.24")



80cm x 180cm (31.49" x 70.86")

TECHNICAL DETAILS

2.

3.

7.

8.

9.

10.

11.

12.

13.

14.15.

18.

1. **Stain Resistance:** Class 4 to Class 5

Chemical Resistance: UB Min to UA ULA UHA UHB

Slip Resistance: R11 A to A+B+C

4. Dynamic Coefficient of Friction (DCOF BOT 3000): ≥

0.42

5. **Bending Strength:** 5076 psi

5. **Breaking Strength in lbs**: 157 lbs (sp < 7.5mm), 292

lbs (sp \geq 7.5mm)

Water Absorption: 0.08%

Resistance to Deep Abrasion: 0.0085 in³

Thermal Shock Resistance: No damage

Surface Quality: 95% min free from visible flaws

Straightness Deviation: ± 0.059 in

Thickness Deviation: ± 0.020 in

Right-Angle Deviation: ± 0.079 in

Flatness: ± 0.079 in

Frost Resistance: No damage

16. **Release of Hazardous Substances:** No variation

17. Bending Strength (Breaking Force in lbs): 3234 lbs

Breaking Force in psi: 6741 psi

FEATURES

The 24x48 and 32x72 porcelain pavers by NT Pavers offer a perfect blend of style and durability for outdoor environments. Each paver, measuring a substantial 24 inches by 48 inches and 32 inches by 72 inches, provides a robust foundation for a variety of outdoor spaces. With a practical thickness, these pavers ensure ease of installation and a smooth, cohesive appearance.

PACKAGING DETAILS

24x48: 1 pallet = 240 sqft (30 pcs/pallet. 1 pc/bx) **32x72:** 1 pallet = 320 sqft (20 pcs/pallet. 1 pc/bx)





DATA SHEET 24X48 & 32X72 PORCELAIN PAVERS



60cm x 120cm (23.62" x 47.24")



80cm x 180cm (31.49" x 70.86")

AVAILABLE COLORS



Platinum Veincut



Pearl Veincut



Chestnut Veincut