



SHOWROOM LINE



Cleaners

TILE CLEANER

Slightly acidic cleaner for the removal of surface patinas and residues.

TILE CLEANER is a slightly acidic, water-based cleaner for deep cleaning of organic and inorganic residues. Its special formula allows the product to penetrate inside the pores and textures of the material. In this way, **TILE CLEANER** is able to dissolve and remove the dirt that has built up on the material, no matter how old or stubborn.

TILE CLEANER is recommended for use on all materials that are acid-resistant.

BENEFITS

- ✓ Concentrated formula
- ✓ Highly effective against the surface patina
- ✓ Great cleaning power
- ✓ Deep extractive action

USES

Suitable for indoor and outdoor applications.

Suitable for Slate, Sandstone, Basaltina - Lava stone, Molten basalt, Glazed ceramics, Clinker, Cotto, Granite, Polished porcelain tiles, Natural porcelain tiles, Textured porcelain tiles, Reconstituted stone (Eco stone), Porphyry, Quarzite, Terracotta, Tuff

COVERAGE

10/15 m²/l

APPLICATION EQUIPMENT

White Pad, Single disk machine

APPLICATION STEPS

Before applying the product it is necessary to take a preliminary test to evaluate the suitability of the product on an unexposed area or unused piece of material

Surface Preparation

- Before proceeding with the cleaning, it is advisable to clean away any surface residues, such as dust, debris, and coarse dirt, using a broom or a vacuum cleaner.
- Protect any surface close by that is not meant to be treated.
- Apply the product to a dry surface with a temperature between +5 e +40°C
- Wait at least 2 days after the installation for the grouting to cure completely

Application

- Dilute the product in clean water. Pour 1 part of product into 2 or 3 parts of water, according to the type of dirt and the severity of the residues.
- Begin to work the product on the surface, using the preferred tool.
- Let the product act for 10 - 20 minutes, working it every now and then to boost its cleaning power.
- Once the time has passed, remove all residues and rinse the whole surface with plenty of water. If the result is only partially achieved, repeat the application process following the same steps and if necessary, slightly increase the concentration of the product in water.

Resume surface use

After carefully removing any residues and rinsing the surface with water, no further action or waiting time is necessary.

MADE IN ITALY

100%



SHOWROOM LINE


**COMPLEMENTARY
MAINTENANCE
PRODUCTS
MANUTENZIONE**

After cleaning with **TILE CLEANER** we recommend using the most suitable Faber cleaner, such as **NEUTRAL CLEANER** or **FLOOR CLEANER**, depending on the nature of the surface.

**INSTRUCTIONS
AND GUIDELINES**

- Do not apply the product on wet or heated surfaces
- When applying to recently laid or grouted surfaces, wait for the adhesive or grout to cure completely.
- Do not use in combination with other chemicals
- Do not apply on acid sensitive materials
- Before applying the product it is necessary to take a preliminary test to evaluate its suitability

**EQUIPMENT
CLEANING**

The equipment used can be cleaned with water

PHYSICAL AND TECHNICAL DATA

Formula	Liquid
Color	Clear
Odor	Lemon
pH	1,5 ± 0,5
Specific gravity at 20°C	1010 ± 10 g/l

STORAGE

Keep the container tightly closed and store in a cool, dry place

SHELF LIFE

36 months in the original, sealed packaging, stored in a cool, dry place

PACKAGING

1 l bottles - 12 bottles per box
5 l bottles - 4 bottles per box

**ACCIDENTAL
SPILLS**

Soak up the product with an absorbent material (paper towels, sawdust, vermiculite, etc.) and dispose of it in the most suitable waste container.

SAFETY

When applying the product, always use suitable personal protective equipment and follow the instructions on the product safety data sheet with care.

Rev6.0 – 12/09/2022

This technical data sheet supersedes all previous versions. Always refer to the latest version of the data sheet, available on www.fabersurfacecare.com site. Faber Chimica reserves the right to update and/or modify the data and information contained in the datasheet.

The information in this data sheet is based on our wide experience in technical and operational research. In any case, you should always make a preliminary test to verify the suitability of the product for the intended use and the type of material on which it will be applied. The information and the suggestions can't be construed as a commitment or result in our responsibility as the conditions and method of use of the product cannot be controlled by us. Therefore Faber Chimica Srl disclaims any liability concerning the use of such data and suggestions.