NT PAVERS

DATA SHEET

ONYX IVORY LEVEL POLISHED

PORCELAIN INTERIOR SLABS

64"x128" | 162 cm x 324 cm | 12 MM

TECHNICAL DETAILS

1. **Thickness:** 12MM (0.472 inches)
2. **Complies with ASTM C373-14** for water absorption: ≤ 0.5%
3. **Breaking strength** according to ASTM C648-04: Average ≥ 275 lbf, with a minimum for each piece of ≥ 250 lbf
4. **Color resistance** to light exposure meets DIN 51094 standards, ensuring no noticeable color changes.
5. **Modulus of rupture** meets the minimum required 5080 psi, with an individual minimum value of 4641 psi.
6. **Chemical resistance** according to ASTM C650-04 shows no effect, ensuring durability against household chemicals and pool salts.
7. **Stain resistance** is classified as Class 5 under ISO 10545-14, indicating the highest resistance level.
8. **Thermal shock resistance** meets ASTM C484 standards, ensuring the slabs withstand sudden temperature changes.
9. **Frost resistance meets ASTM C1026, indicating no damage from freeze/thaw cycles.**

FEATURES

Discover the transformative allure of our 12mm thick interior porcelain slabs, a perfect blend of timeless beauty and modern practicality. These slabs stand out for their robust durability and stunning aesthetic, making them ideal for creating sophisticated and elegant environments in homes and commercial spaces alike.

Bookmatch A

Bookmatch B