



DATA SHEET

24X24

PORCELAIN PAVERS

24"x24"

60cm x 60cm
(23.62" x 23.62")

TECHNICAL DETAILS

- 1. Breaking Strength (EN ISO 10545-4): $\geq 2,923$ lbs (≥ 1300 N).**
- 2. Modulus of Rupture (EN ISO 10545-4): $\geq 7,252$ psi (≥ 50 N/mm²).**
- 3. Water Absorption (EN ISO 10545-3): $\leq 0.5\%$.**
- 4. Resistance to Deep Abrasion (EN ISO 10545-6): ≤ 175 mm³.**
- 5. Thermal Shock Resistance (EN ISO 10545-9): Resistant.**
- 6. Frost Resistance (EN ISO 10545-12): Resistant.**
- 7. Chemical Resistance (EN ISO 10545-13): GA (Resistant to low concentrations of acids and alkalis).**
- 8. Stain Resistance (EN ISO 10545-14): Class 5.**
- 9. Linear Thermal Expansion (EN ISO 10545-8): $\leq 6.5 \times 10^{-6}$ °C⁻¹.**
- 10. Slip Resistance (DIN 51130): R11.**
- 11. Slip Resistance (DIN 51097): C.**
- 12. Dynamic Coefficient of Friction (ANSI A 137.1): ≥ 0.60 .**

FEATURES

The 24x24 porcelain pavers by NT Pavers offer a perfect blend of style and durability for outdoor environments. Each paver, measuring a substantial 24 inches by 24 inches, provides a robust foundation for a variety of outdoor spaces. With a practical thickness, these pavers ensure ease of installation and a smooth, cohesive appearance.

PACKAGING DETAILS

24x24: 1 pallet = 240 sqft (64 pcs/pallet. 2 pcs/bx)

DATA SHEET
24X24
PORCELAIN PAVERS



24"x24"

60cm x 60cm
(23.62" x 23.62")

AVAILABLE COLORS




Rustic Grigio



Soft Cream



Pietra Grey



Forge



Pocono